




Sliding Door Hardware




SIMPLE, DEPENDABLE, HONEST, - HAGER COMPANIES SLIDING DOOR HARDWARE

In our effort to streamline our SDH offering and make it easier to do business with Hager, we have enhanced quality and performance and significantly reduced leads times. As part of this new consolidated line, and for your convenience, we have created a quick cross-reference guide to highlight the changes.

**Please note: The components are between new and previous versions/
consolidated series are non-interchangeable.**

	CONSOLIDATED SERIES	NEW PART NUMBER
BI-FOLD SET	9570, 9860, 9861, 9890, 9891	9570RC
BY-PASS SET	9675, 9676, 9611, 9110 9130, 9612, 9875 9514, 9583 9614, 9683	9611CS 9611HD 9613RS 9614RS
WALL MOUNT SET	9710	9710HD
POCKET DOOR SETS	9678, 9110 9878, 9130, 9901	9878CS 9878HD

SLIDING BARN DOOR HARDWARE



- 9456 - Top Mount
- 9457 - Face Mount

eCONESTOGA - ECONOMY SERIES BARN DOOR HARDWARE

- Durable powder-coated steel
- Door weight up to 250 lbs
- Wood door 1-3/4" maximum thick

System Includes

- Black steel flat rail (72" or 96")
- Two hangers
- Two end stops
- Two anti-jump disks
- One channel guide pair
- One fin guide

Standards

Meets performance requirements ANSI/BHMA A156.14 (Grade 1) for sliding doors by exceeding 100,000 cycles
Type: D02111-250

Applications

- Assisted Living
- Hospitality
- Multi-Family
- Office & Retail
- Residential



- 9432 - Top Mount
- 9436 - Face Mount

9400 SERIES - STAINLESS STEEL DOOR HARDWARE

- 304 stainless steel track and hangers with nylon coated rollers
- Door weight up to 250 lbs
- Wood door 1-3/4" thick (top-mount hangers)
- Door bottom 3/8" undercut
- Glass doors 3/8" to 1/2" thick

System Includes

- Stainless steel track (78" or 96"*) with two end caps - available in round rail
- Hangers with wall brackets
- One door bottom guide
- Two track stops
- Mounting and installation hardware

Standards

Meets performance requirements ANSI/BHMA A156.14 (Grade 1) for sliding doors by exceeding 100,000 cycles
Type: D02111-250

Applications

- Commercial
- Hospitality
- Multi-Family
- Office & Retail
- Residential

SLIDING DOOR - WALL-MOUNT



9710HD SERIES WALL-MOUNT SLIDING DOOR HARDWARE

- Door weight up to 250 lbs
- Door thickness 1-1/8" - 1-3/4"
- Easy glide 4-wheel ball bearing carriers -9 6
- Fastener concealment
- Available in lengths 72", 96" & 144"
- Available in anodized aluminum and black

System Includes

- Aluminum wall-mount track
- Fascia
- Two end caps
- Two Hangers
- Hardware

Standards

Meets performance requirements ANSI/BHMA A156.14 (Grade 1) for sliding doors by exceeding 100,000 cycles

Type: D02111-250

Applications

- Commercial
- Healthcare
- Hospitality
- Office
- Residential

SLIDING DOOR HARDWARE - ACCESSORIES



9458 BARN DOOR PRIVACY LOCK

Compliments the 9400 Stainless steel and eConestoga Series Sliding Door Hardware

Applications

- Assisted Living Facilities
- Hospitality
- Multi-Family



9459 SURFACE JAMB MOUNT

Compliments the 9400 Stainless steel and eConestoga Series Sliding Door Hardware

Applications

- Assisted Living Facilities
- Hospitality
- Multi-Family

POCKET DOOR HARDWARE



9878CS - POCKET DOOR KIT (FRAMING NOT INCLUDED)

- Door weight up to 150 lbs per panel bi-fold
- Door thickness from 1-1/8" - 1-3/4"
- Track is extruded aluminum jump-proof style with integral
- Available in lengths: 72" & 96"

System Includes

- Aluminum track
- Two hangers
- Pair of door guides
- One bumper
- Parts bag
- Optional soft close (1-269-8651) for doors up to 150 lbs.

Certifications

- Conforms to ANSI A156.14
- Type: D02321-150

Applications

- Commercial
- Healthcare
- Hospitality
- Office
- Residential



9878HD - POCKET DOOR KIT (FRAMING NOT INCLUDED)

- Door weight up to 250 lbs per door
- Door thickness from 1-1/8" - 1-3/4"
- Track is extruded aluminum jump-proof style with "V" shaped rails
- Available in lengths: 72" & 96"

System Includes

- Aluminum track
- Parts bag
- Two hangers
- Pair of door guides
- One bumper

Certifications

- Conforms to ANSI A156.14
- Type: D02321-250

Applications

- Commercial
- Healthcare
- Hospitality
- Office
- Residential

POCKET DOOR FRAME KITS



9600 SERIES COMMERCIAL POCKET DOOR FRAME KITS 9628CS | 9629CS | 9630CS | 9631CS

- V-groove jump proof aluminum track
- Pre-assembled header assembly goes up quickly
- Real wood split studs, size 3/4" x 1-3/4" width relative to length, steel encased for rigidity and to prevent fastener penetration into the pocket
- 2 pairs of split studs with wood inserts

Certifications

- Meets performance requirements ANSI/BHMA A156.14 (Grade 1) for sliding doors by exceeding 100,000 cycles in operation
- Type: D02311-150
- ADA Compliant

PART #	MAX DOOR WEIGHT	DOOR THICKNESS	DOOR WIDTH	DOOR HEIGHT	HANGER
9628CS	150 lbs (68 kg)	1-3/8" - 1-3/4" (35mm-44mm)	3'0" (914mm)	9'0" (2743mm)	9805
9629CS	150 lbs (68 kg)	1-3/8" - 1-3/4" (35mm-44mm)	3'0" (914mm)	8'0" (2438mm)	9805
9630CS	150 lbs (68 kg)	1-3/8" - 1-3/4" (35mm-44mm)	3'0" (914mm)	7'0" (2134mm)	9805
9631CS	150 lbs (68 kg)	1-3/8" - 1-3/4" (35mm-44mm)	3'0" (914mm)	6'8" (2032mm)	9805

For doors in excess of 150 lbs, we recommend the use of our 9850HD or 9852HD Pocket Door kits.

POCKET DOOR FRAME KITS



9800 SERIES HEAVY-DUTY POCKET DOOR FRAME KITS 9850HD for 2" x4" Walls | 9852HD for 2" x 6" Walls

- For doors 1-3/8" - 1-3/4" thick, weighing up to 250 lbs.
- Pre-assembled header assembly goes up quickly
- Heavy-duty, V-groove jump proof aluminum track
- Real wood split studs, size 3/4" x 1-3/4" width relative to length, steel encased for rigidity and to prevent fastener penetration into the pocket

Certifications

- Meets performance requirements ANSI/BHMA A156.14 (Grade 1) for sliding doors by exceeding 100,000 cycles in operation
- Type: D01311-250
- ADA Compliant

PART #	MAX DOOR WEIGHT	DOOR THICKNESS	DOOR WIDTH	DOOR HEIGHT	HANGER
9850HD-102	250 lbs (113 kg)	1-3/8" - 1-3/4" (35mm-44mm)	4'0" (1219mm)	8'6" (2743mm)	9806 Ball bearing
9850HD-96	250 lbs (113 kg)	1-3/8" - 1-3/4" (35mm-44mm)	4'0" (1219mm)	8'0" (2438mm)	9806 Ball bearing
9852HD-84	250 lbs (113 kg)	1-3/8" - 1-3/4" (35mm-44mm)	3'0" (914mm)	7'0" (2134mm)	9806 Ball bearing
9852HD-80	250 lbs (113 kg)	1-3/8" - 1-3/4" (35mm-44mm)	3'0" (914mm)	6'8" (2032mm)	9806 Ball bearing

BI-FOLD SETS



9570CS

- Door weight up to 125 lbs per panel bi-fold
- Door thickness from 1-1/8" - 1-3/4"
- Track is extruded aluminum jump-proof style with "V" shaped rails
- Available in lengths: 36", 48", 60", 72", & 96"

System Includes

- Aluminum track
- Parts bag (additional parts bag required for 4-door application)

Applications

- Commercial
- Healthcare
- Hospitality
- Office
- Residential

BY-PASS PACKED SETS



9613RS Non-Fascia

- Door weight up to 60 lbs per door with single wheel hanger
- Door thickness 3/4" - 1-3/8"
- Track is extruded aluminum jump-proof style with integral
- Available in lengths: 48", 60", 72", & 96"

System Includes

- Aluminum track
- Four hangers
- Two pulls
- Parts bag (additional parts bag required for 3-door application)


Certifications

- Conforms to ANSI A156.14
- Type: D02411-75

Applications

- Commercial
- Healthcare
- Hospitality
- Office
- Residential

BY-PASS PACKED SETS



9614RS Fascia

- Door weight up to 60 lbs per door with single wheel hanger
- Door thickness 3/4" - 1-3/8"
- Track is extruded aluminum jump-proof style with integral
- Grooved fascia
- Available in lengths: 48", 60", 72" & 96"

System Includes

- Aluminum track with fascia
- Four hangers
- Two pulls
- Parts bag (additional parts bag required for 3-door application)

Certifications

- Conforms to ANSI A156.14
- Type: D02411-75

Applications

- Commercial
- Healthcare
- Hospitality
- Office
- Residential



9611CS

- Door weight up to 150 lbs per door
- Door thickness up to 1-3/8" - 1-3/4"
- Quick release hangers allow for easy door hanging and removal
- Available in lengths: 48", 60", 72", 96", & 120"

System Includes

- Two aluminum tracks
- Four hangers - 9 5
- One guide
- Two pulls
- Parts bag (additional parts bag required for 4-door application)

Certifications

- Conforms to ANSI A156.14
- Type: D02411-150

Applications

- Commercial
- Healthcare
- Hospitality
- Office
- Residential

BY-PASS PACKED SETS



9611HD

- Door weight up to 250 lbs per door
- Door thickness up to 1-3/8" - 1-3/4"
- Quick release hangers allow for easy door hanging and removal
- Available in lengths: 48", 60", 72", 96", & 120"

System Includes

- Two aluminum tracks
- Four hangers -9 6
- One guide
- Two pulls
- Parts bag (additional parts bag required for 4-door application)

Certifications

- Conforms to ANSI A156.14
- Type: D02411-250

Applications

- Commercial
- Healthcare
- Hospitality
- Office
- Residential