

## 3300 Series Lever

### Grade 3 Tubular Lever

#### Applications:

- Multi-Family
- Assisted Living Facilities
- Hospitality

#### Features:

- Field reversible (with the exception of 3317 Johnston)
- Thru-bolt design for ease of installation
- Standard 4-way latch provides versatility for most retrofit applications

#### Warranty:

- One-year warranty



## PRODUCT SPECIFICATIONS

#### CERTIFICATIONS:

- BHMA Certified ANSI A156.2, Grade 3 test standards
- ADA Compliant ANSI A117.1

#### EXPOSED TRIM:

- Levers: Cast zinc
- Rose: Wrought brass

#### ROSE DIAMETER:

- 2-9/16" (65mm)

#### DOOR THICKNESS:

- 1-3/8" to 1-3/4" (35mm to 45mm)

#### BACKSET:

- 2-3/8" to 2-3/4" (60mm to 70mm) adjustable backset

#### LATCHBOLT:

- 1/2" (13mm) Throw-- Zinc
- 1" x 2-1/4" (25mm x 57mm) faceplate
- 4-way Latch Design (Square Corner and Round Corner provided)

#### STRIKES:

- Round Corner Full Lip - Standard
- Square Corner Full Lip and Tee Strike available separately

#### LEVER OPTIONS:

- Archer, August, Johnston, Withnell

#### FINISHES:

- US3\* (605), US10B (613), US15 (619), US26\* (625), US26D (626)
- \* *Non-stocked finishes*

#### FUNCTIONS:

- [10-Passage](#), [17-Single Dummy](#), [40-Privacy](#), [53-Entry](#)

#### KEYING/KEYWAY:

- 5-Pin brass cylinder only, keyed different (KD) only, Schlage C keyway only, (2) cut keys provided. *No other key options available.*

#### DOOR PREP:

- 2-1/8" diameter (bore), Latch hole: 1" diameter (cross bore)

#### PACKAGING:

- Box packed

#### WARRANTY:

- One-year