

## 29EA Door Prop Alarm Key Switches



### Description:

- Provides audible alarm when a door is accessed or left open
- Installs in single gang or double gang enclosures
- Compatible with U.S. standard 1.125" and 1.25" mortise key cylinders and interchangeable core cylinders (sold separately)

## PRODUCT SPECIFICATIONS

### FUNCTIONS:

- N - No Key Switch
- M - Mortise Cylinder Switch (sold separately)
- K - Key Switch

### FEATURES:

- Audible sirens with adjustable timer settings
- Bypass status indicator light
- Vandal-resistant aluminum construction with security screws
- Optional key switch or mortise cylinder
- Adjustable timed delay
- Exit alarm on door opening
- Automatic or manual alarm reset
- Output relays
- Integral bi-color LED status indicator
- Compact universal mounting
- 85dB Piezo buzzer alarm

### INPUT:

- 12 or 24 VDC
- Trigger input: Dry, N/O, or N/C (selectable by onboard jumper), door contact (sold separately)
- Remote Reset/Bypass input: Dry, N/O, or N/C. Reset by momentarily shorting the input when alarmed. Bypass by shorting and holding the input when secure

### OUTPUT:

- Alarm output: Form C, 2A @ 30VDC max
- Auxiliary output: Form C, 2A @ 30VDC max. Follows door contact input or alarm output (field selectable)

### LED INDICATORS:

- Green - normal operation
- Red - alarm activated

### CYLINDER:

- 3902 - 1/1/8" recommended (order separately)
- HS4 - HG02 GEO mortise cylinder