

# 1256

## Single Acting Square Corner Set

### Application:

- ANSI K81071F
- For maximum versatility use all spring hinges or a combination of spring hinges and ball bearing hinges. Do not use plain bearing hinges.
- Full spring tension may not be required on all hinges
- Strong wind conditions, drafts, carpeting drag, twisted/misaligned frames, or weatherstripping on doors may require additional spring hinges



## PRODUCT SPECIFICATIONS

### INCLUDES:

- Two (2) each 1250 spring hinge and one (1) each BB1279 ball bearing hinge

### MATERIAL:

- Steel with steel components ANSI K81071F

### FINISHES:

- USP, US3, US4, US10B, US26D

### RECOMMENDED MAX DOOR WEIGHT:

- 115 pounds

### DOOR THICKNESS:

- For use on 1-3/4" (45 mm) thick doors

### NOTES:

- Hager does not recommend using spring hinges on doors over 70"

## PRODUCT SIZE OPTIONS

HINGE SIZE (INCHES)	HINGE SIZE (MM)	GAUGE OF METAL	HOLE COUNT	SCREW SIZE (MACHINE)	SCREW SIZE (WOOD)
4-1/2 x 4	114 x 102	0.134	8	1/2 x 12-24	1-1/4 x 12
4-1/2 x 4-1/2	114 x 114	0.134	8	1/2 x 12-24	1-1/4 x 12

SERIES 1 3/4" (45MM) DOOR	SIZE	RCM MAX DOOR WT. (LBS)	SPRING HINGE	BALL BEARING HINGE
1150	4 1/2 x 4 & 4 1/2 x 4 1/2	70	1	2
1150	4 1/2 x 4 & 4 1/2 x 4 1/2	115	2	1
1150	4 1/2 x 4 & 4 1/2 x 4 1/2	150	3	---
1250	4 1/2 x 4 & 4 1/2 x 4 1/2	70	1	2
1250	4 1/2 x 4 & 4 1/2 x 4 1/2	115	2	1
1250	4 1/2 x 4 & 4 1/2 x 4 1/2	150	3	---
1256	4 1/2 x 4 1/2	115	2	1
1255	4 1/2 x 4 1/2	115	2	1