

## 4500 Series Rim

### Grade 1 Rim Device

#### Applications:

- Heavy Duty Commercial

#### Certifications:

- ANSI/BHMA A156.3-2014 Grade 1
- UL305 Listed for Panic Hardware
- UL/cUL Listed for up to 3 hours for "A" label single doors
- UL10C Positive Pressure Rated
- UL10B Neutral Pressure Rated
- Warnock Hersey listed for up to 3 hours with fire rated removable mullion
- Complies with ANSI A117.1 for accessible buildings and facilities
- Miami-Dade County, Florida NOA #17-1226.23, Exp. Aug. 16, 2022.



## PRODUCT SPECIFICATIONS

#### TRIM:

- Archer, August, Charles, Johnston, Joshua, Louis, Warren, William or Withnell lever with escutcheon
- Pull plate trim
- Rim cylinder x optional pull

#### COVERS:

- Stainless steel, zinc

#### COVER TUBE:

- Aluminum

#### END CAPS:

- Standard end cap (zinc)
- **OPTIONAL** Flush end cap (zinc)

#### DOOR WIDTH:

- 36" (914 mm) field sizeable to 30" (762 mm) panic-rated door and 28" (711 mm) fire-rated door
- 48" (1219 mm) field sizeable to 36" (914 mm) panic- or fire-rated door
- Reference [electrified exit device](#) for door width specifications

#### DOOR THICKNESS:

- 1-3/4" (44 mm) - Standard up to 3", except with night latch which is 2-1/2"

#### STILE WIDTH:

- 5-3/8" (137 mm) - Minimum stile width required for single doors and standard 5/8" (16 mm) stop
- 4-7/8" (124 mm) - Minimum stile width required for double door x surface vertical rod with double door strike
- 5-3/4" (146 mm) - Minimum stile width required for double door and 2" (51 mm) mullion
- All stile widths are measured from the door edge

#### FASTENERS:

- Wood and machine screws
- Thru-bolts

#### LATCHBOLT:

- 3/4" (19 mm) throw, pullman type with automatic dead-latching, stainless steel

#### PUSH BAR:

- **OPTIONAL** Photoluminescent push bar cover available

#### STRIKES:

- Stainless steel with plated rollers - Included standard with panic devices
- Solid stainless steel - Included standard with fire-rated devices
- Surface applied to frame with slotted holes for easy adjustment
- Double door strike for use with surface vertical rod and rim device available

#### FINISHES:

- US3, US4, US10, US10B, US26, US26D, US32D, BLK

#### DOGGING:

- Hex key dogging standard on panic rated devices
- Cylinder dogging available on panic rated devices, specify "CD" (3902 1-1/8" (29 mm) mortise cylinder sold separately)

#### PROJECTION:

- 3" (76 mm) in undogged position
- 2-5/8" (67 mm) in dogged position

#### NOTES:

- Recommended to be used on appropriately reinforced doors

#### EPD:

- [4500 Exit Device Environmental Product Declaration](#)