

2-679-0621

2 Conductor,
Alum. Powder Coat Power Transfer

Features:

- Two (2) 18 ga. wires, 5 amp @ 12/24 V AC/DC
- Power control, input for electric locks and exit devices, locked, latched, mantrap, forced entry, open status signal wiring
- Mortise door and frame installation
- PTM is completely concealed when the door is closed
- All metal design with stainless steel tubular wire transfer and heavy cast housing with steel back boxes provide weather and tamper resistance when door is open or closed
- Fasteners for wood, steel, and aluminum doors and frames included
- UL Listed Miscellaneous Fire Door Accessories
- UL 10C Listed for up to 3 hours on fire rated doors and frames
- Classified according to Uniform Building Code (UBC) Standard 7-2, Fire Test of Door Assemblies (1997)



PRODUCT SPECIFICATIONS

COMPATIBLE OPENINGS:

- 1-3/4" (44 mm) thick doors
- 0-180 degree opening swing with up to 3/4" (19 mm) offset pivots
- 0-180 degree opening swing with up to 5" wide butt hinges
- 0-130 degree opening swing with up to 5-1/2" (140 mm) wide butt hinges
- 0-130 degree opening swing with up to 6" (152 mm) wide butt hinges
- Not compatible with center hung doors, swing clear hinges, pocket pivots, butt hinges larger than 6" (152 mm), and 1-1/2" (38 mm) offset pivots

DIMENSIONS:

- 9" (h) x 1-1/4" (w) x 1-5/8" (d)
- 229 (h) x 32 (w) x 41 (d) mm