

## 4801

### Non-Latching Push Bar



#### Description:

- Non-latching pressure sense push bar
- Used for magnetic lock release, access control request-to-edit, delayed egress trigger, alarm shunt, CCTV activation or alarm activation



### PRODUCT SPECIFICATIONS

#### FEATURES:

- Tri-Failsafe
- Temperature Tolerant
- Human touch not required
- Sensor calibration not required
- Field installed sign - 1" green letters
- Heavy Duty Construction
- Narrow, low profile
- Two outputs - Two dry contacts for lock release, request to exit, alarm shunt, alarm activation
- Armored power loop
- 10 ft. cable
- No moving parts, quick and quiet operation

#### FINISHES:

- ALM (Standard)
- BLK

#### OPTIONS:

- Power transfer loop supplied with bar
- Additional power transfers available

#### DIMENSIONS:

- 36" x 1-7/8" projection standard
- 42" and 48" available
- Bars may be field cut

#### VOLTAGE INPUT:

- 12/24VDC Voltage sensing (No field adjustment)

#### CURRENT:

- 20mA at rest, 115 mA active

#### OUTPUT:

- Two SPDT dry contacts, 3 Amp @ 28VDC

#### ACTIVATION FORCE:

- Factory set at 5 lbs. (2.2 kg)
- Field adjustable up to 15 lbs. (6.8 kg)