

1

03/25/2008

Notes:

1. The maximum swing for both doors can be no more than 105°


For Website

2. Extension rods may be used in cases where certain openings need to be obtained

Note: If dimension X or Y is not on the chart, interpolate dimension Z. For example, if X = 5 and Y = 36, Z = 30 9/16 + (30 3/4 - 30 9/16)/2 = 30 21/32"

DOUBLE DOOR FLOOR MOUNTING - LOCATION Z																							
		Y = DOOR WIDTH (in)																					
		28		30		32		34		36		38		40		42		44		46		48	
Z &	2	22	3/4	24	3/4	26	3/4	28	3/4	30	3/4	32	3/4	34	3/4	36	3/4	38	3/4	40	3/4	42	3/4
WEEN DOOR	4	22	3/4	24	3/4	26	3/4	28	3/4	30	3/4	32	3/4	34	3/4	36	3/4	38	3/4	40	3/4	42	3/4
BETA	6	22	1/2	24	1/2	26	9/16	28	9/16	30	9/16	32	9/16	34	9/16	36	9/16	38	5/8	40	5/8	42	5/8
	8	22	1/8	24	3/16	26	3/16	28	1/4	30	1/4	32	5/16	34	5/16	36	3/8	38	3/8	40	3/8	42	3/8
ANCE S TO 3 (in)	10	21	1/2	23	5/8	25	11/16	27	13/16	29	7/8	31	7/8	33	15/16	36		38	1/16	40	1/16	42	1/8
S DISTANCE DOORS TO JAMB (in)	12	31 3/8 33 7/16 35 1/2 37 9/16 39 5/8 41											41	11/16									
	14	CAUTION: IF DIMENSIONS X AND Y INTERSECT IN THIS BLANK AREA,																					
CENTER E TWO D	16																						
X = CI	18		THE CATCH PLATE ASSEMBLY AND DOOR MAGNET WILL NOT ALIGN WITHOUT USE OF ADDITIONAL EXTENSION RODS																				
×⊢	20							<u> </u>	J. 01 /				2,13101										

DOUBLE DOOR FLOOR MOUNTING - LOCATION Z														
	Y = DOOR WIDTH (mm)													
		711.2	762.0	812.8	863.6	914.4	965.2	1016.0	1066.8	1117.6	1168.4	1219.2		
Z &	50.8	577.9	628.7	679.5	730.3	781.1	831.9	882.7	933.5	984.3	1035.1	1085.9		
VEE 000	101.6	577.9	628.7	679.5	730.3	781.1	831.9	882.7	933.5	984.3	1035.1	1085.9		
BETWEEN THE DOOR	152.4	571.5	622.3	674.7	725.5	776.3	827.1	877.9	928.7	981.1	1031.9	1082.7		
n)	203.2	562.0	614.4	665.2	717.6	768.4	820.7	871.5	923.9	974.7	1025.5	1076.3		
ANCE IS TO 1 (mm)	254.0	546.1	600.1	652.5	706.4	758.8	809.6	862.0	914.4	966.8	1017.6	1070.0		
R DISTAI DOORS JAMB (r	304.8	796.9 849.3 901.7 954.1									1006.5	1058.9		
ER I	355.6	99												
CENTER E TWO D	406.4		CAUTION: IF DIMENSIONS X AND Y INTERSECT IN THIS BLANK AREA, THE CATCH PLATE ASSEMBLY AND DOOR MAGNET WILL NOT ALIGN											
X = CE THE	457.2		IHE			Y AND DOO ADDITIONAL			LIGN					
× -	508.0			WITHO	OT OSE OF	ADDITIONAL	LATENSIO	NOD3						



4

3


2

1

В

1 2 3 4 Note:

1. Extension rods may be used in cases where certain openings need to be obtained



Instructions:

- 1. Determine the Desired Maximum Door Opening Angle. This must be less than or equal to the maximum door opening angle permitted by the door closer, trim and partition.
- 2. Open the door at that angle
- 3. Line up the Door, Catch Plate Assembly and Door Magnet as seen in the drawing above
- 4. Mount the Door Magnet to the floor at that location



D

PROPRIETARY & CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HAGER COMPANIES ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HAGER COMPANIES IS PROHIBITED.

HAGER RESERVES
THE RIGHT TO MAKE
DESIGN CHANGES
WITHOUT NOTICE.
CALL HAGER
ENGINEERING AT
1-800-325-9995
FOR THE LATEST
REVISION DATE OF
TEMPLATE.

(E ALL C		DRAWN BY:	MA	9/29/2021	SERIES NO.	PA	ART NO.	_		
	ALL DIMENSIONS REFERENCE UNLESS	ENG. APPR.: DF 9/29/202		9/29/2021	380		380G			
	TOI FRANCE SPECIFIED.	MM/DD/YYYY			PART DESCRIPTION:					
	TOLERANCE SPECIFIED.	THIRD ANGLE PROJECTION			Floor Mount (Single Door): Door Magnet					
		MATERIAL:			Mounting Location					
	UNITS: INCH = AUTHORITY				DRAWING NO.			REVISION		
:	[] = MILLIMETER REFERENCE	FINISH:				03				
	DO NOT SCALE	WEIGHT:			SHEET SIZE: A	SCALE: 1:9	9 SH	EET 2 OF 2		