INSIDE

2 3/4"
[70]

1 1/2"
[38]

9/16"
[14]

1 1/8"
[28]

Ø1"
[25]
DRILL TO
MORTISE

Ø3/8"
[10]
DRILL TO MORTISE
RH & RHR
(2 PLACES)

9/16"
[14]

1 1/8"
[28]

1 1/4" +1/32" -0"
[31.8 +0.8 0]

7 1/4"
[184]

3 5/8"
[92]

5 3/4"
[146]

2 7/8"
[73]

3 5/8"
[92]

2 7/8"
[73]

3/8"
[10]

4"
[102]

8" +1/32" -0"
[203.2 +0.8 0]

4"
[102]

℄ OF STRIKE

℄ OF
LOCK BODY

R1/2"
[13]

Ø3/16" [4] ▽ 9/16"[14]
#12-24 TAP
WOOD: PRE-DRILL Ø1/8" HOLES
(2 PLACES)

OUTSIDE

4 1/2"
[114]

7/32"
[6]

2 3/4"
[70]

Ø1 1/4" CYL. HOLE
[32]
DRILL TO MORTISE

2 1/8"
[54]

(RH, RHR SECTIONAL SHOWN)

HAGER RESERVES THE RIGHT TO MAKE DESIGN CHANGES WITHOUT NOTICE. CALL HAGER ENGINEERING AT 1-800-325-9995 FOR THE LATEST REVISION DATE OF TEMPLATE.

MATERIAL Material <not specified>

FINISH

DO NOT SCALE DRAWING

DRAWN	TJS	9/21/07
ENG. APPR.	-	-
Q.A.		

TOLERANCES:
FRACTIONAL: ±0.015"
ANGULAR: MACH:± 1° BEND:±1°
TWO PLACE DECIMAL: ±0.01"
THREE PLACE DECIMAL: ±0.004"

3800
3800 SECTIONAL DOOR PREP,
FUNCTION: 80 LOT

SIZE **A**

DWG. NO. **T-LS00771**

REV. **04**

SCALE:1:4   WEIGHT: 4.95   SHEET 10 OF 14

HAGER COMPANIES
ST. LOUIS, MISSOURI