

SIZE: 5 3/4 (146.05) FOR 1 3/4 (44.45) DOOR

6 3/8 (161.93)

5 3/4 (146.05) FRAME

5 3/8 (136.53)

1 (25.40)

1 5/8 (41.28)

45° TYP

.089 (2.26)

1/2 (12.70)

DOOR & FRAME C

1 3/4

(44.45)

1 7/8

(47.63)

1 7/8

(47.63)

5/16 (7.93)

2 3/4
(69.85)

2 1/8
(53.98)

5/16 (7.93)

TOP

C

C

1 1/4
(31.75)

.251 (6.38)

.688 (17.48)

7/8 (22.23)

R.H. DOOR SWING INSTALLATION SHOWN

LEFT HAND OPPOSITE

-DO NOT SCALE-

CATALOG NUMBER	MATERIAL
455	BRASS

ALL NON-BRACKETED DIMENSIONS ARE IN INCHES, ALL BRACKETED DIMENSIONS ARE IN MILLIMETERS.

Machine Screw Size
8-32 x 1/2" undercut F.H.

CUTOUT IN METAL JAMB FOR DOUBLE-LIPPED STRIKE

2 5/16 (58.74)
MIN. CLEARANCE FOR DOOR STOP COVER CENTERED

2 25/32 (70.64)

3/16 (4.76)

BACK-UP PLATES (2)
(SUPPLIED BY OTHERS)

NOTE: Horizontal centerline of plate to coincide with horizontal centerline of cutout.



HAGER COMPANIES
139 Victor St.
St. Louis, MO 63104
1-800-325-9995

HAGER RESERVES THE RIGHT TO MAKE DESIGN CHANGES WITHOUT NOTICE.

DESCRIPTION:

5-3/4" COMBINATION RESCUE DOOR STOP AND TWO WAY STRIKE FOR CENTER HUNG DOORS

NO.	REVISION	BY	DATE
3	PER ECO CT08036	SEW	11-03-08

PART NO.

T366