

THIS SIDE UP FOR LHR DOOR

4700 RIM FIRE RATED EXIT DEVICE FIRE RATED REMOVEABLE MULLION TEMPLATE FOR USE WITH 4916 FIRE RATED STRIKE & HOOK (FOR FIRE RATED DEVICES ONLY)

DWG NO: T-ED00327 (REV: 01)

SEE OTHER SIDE FOR STANDARD TEMPLATE

(2x) METAL: DRILL/TAP FOR 1/4"-20 MACHINE SCREWS.
WOOD: PRE-DRILL 1/8" HOLES.

(3x) METAL: DRILL/TAP FOR 1/4"-20
MACHINE SCREWS.

DRILL/TAP FOR 1/4"-20 AND
INSTALL SCREW AFTER
FINAL ADJUSTMENTS.

FOLD HERE
CAUTION
DO NOT USE DOOR EDGE!

PLACE THIS SIDE ON MULLION STOP
PLACE THIS SIDE ON DOOR

"A" LABELED HOLES:
(2x) METAL: DRILL/TAP FOR 1/4"-20 MACHINE SCREWS.
THROUGH BOLTS: DRILL 5/16" CLEARANCE HOLES ON PUSH SIDE,
DRILL 3/8" HOLES ON PULL SIDE

"B" LABELED HOLES - THROUGH BOLT ONLY:
(2x) DRILL 5/16" CLEARANCE HOLES ON PUSH SIDE,
DRILL 3/8" HOLES ON PULL SIDE (IF USING TRIM
DRILL 1/2" HOLES)

(2x) METAL: DRILL/TAP FOR 1/4"-20 MACHINE SCREWS.
WOOD: PRE-DRILL 1/8" HOLES.
THROUGH BOLT: DRILL 5/16" CLEARANCE HOLE ON
PUSH SIDE, 3/8" HOLE ON PULL SIDE.

1/2" CLEARANCE HOLE FOR BE, CE, & NL TRIM.
NOT REQUIRED FOR DUMMY TRIM.

DEVICE & STRIKE ϕ

AFTER EXIT DEVICE IS CUT AND
MOUNTED, INSTALL END CAP
BRACKET CENTERED ON DEVICE ϕ .

40" [1016]
RECOMMENDED HEIGHT MAY BE
DETERMINED BY DESIGN SPEC'S

FINISHED FLOOR

 HOLE LOCATIONS

PRIMARY DIMENSIONS SHOWN IN INCHES,
DIMENSIONS IN [] ARE MILLIMETERS.

THIS SIDE UP FOR RHR DOOR

