


NOTES:

1. Although function 27 has dummy levers, the $\phi 1"$ thru hole is still required to accommodate the shape of the spring cages.

(RH, RHR SECTIONAL SHOWN)

 <p>PROPRIETARY & CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HAGER COMPANIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HAGER COMPANIES IS PROHIBITED.</p>	<p>HAGER RESERVES THE RIGHT TO MAKE DESIGN CHANGES WITHOUT NOTICE. CALL HAGER ENGINEERING AT 1-800-325-9995 FOR THE LATEST REVISION DATE OF TEMPLATE.</p>	DRAWN	TJS	9/21/07	<p>3800</p> <p>3800 SECTIONAL DOOR PREP, FUNCTIONS: 27</p>			
		ENG. APPR.	-	-				
		MATERIAL	Material <not specified>			Q.A.		
		FINISH	DO NOT SCALE DRAWING			<p>TOLERANCES:</p> <p>FRACTIONAL: $\pm 0.015"$</p> <p>ANGULAR: MACH: $\pm 1^\circ$ BEND: $\pm 1^\circ$</p> <p>TWO PLACE DECIMAL: $\pm 0.01"$</p> <p>THREE PLACE DECIMAL: $\pm 0.004"$</p>		
		SIZE	DWG. NO.		REV.			
		A	T-LS00771		04			
		SCALE: 1:4	WEIGHT: 5.02		SHEET 2 OF 14			